



Electric

Supply voltage:

372143 (Z7FREH2E0N)	230 V/3 ph/50/60 Hz
372080 (Z7FREH2E00)	380-400 V/3N ph/50/60 Hz

Total Watts:

17.4 kW

Predisposed for:

Key Information:

Usable well dimensions (width):	240 mm
Usable well dimensions (height):	235 mm
Usable well dimensions (depth):	420 mm
Well capacity:	10 lt MIN; 12 lt MAX
Thermostat Range:	105 °C MIN; 185 °C MAX
Net weight:	45 kg
Shipping weight:	
372143 (Z7FREH2E0N)	54 kg
372080 (Z7FREH2E00)	50 kg
Shipping height:	
372143 (Z7FREH2E0N)	540 mm
372080 (Z7FREH2E00)	530 mm
Shipping width:	820 mm
Shipping depth:	860 mm
Shipping volume:	
372143 (Z7FREH2E0N)	0.4 m ³
372080 (Z7FREH2E00)	0.37 m ³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Certification group:

372143 (Z7FREH2E0N)	N7FE2
372080 (Z7FREH2E00)	EF17212