

Modular Cooking Range Line EVO700 Two Wells Freestanding Electric Fryer 14 liter

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



372085 (Z7FREH2FF0)

14+14-It electric fryer with 2 wells and 2 baskets (internal heating elements) - free standing

372144 (Z7FREH2FFN)

14+14-It electric fryer with 2 wells and 2 baskets (internal heating elements) - free standing

Short Form Specification

Item No.

To be installed on height adjustable feet in stainless steel. High efficiency tilting incoloy armoured heating elements (17.4kW) placed inside the wells. Deep drawn wells. Oil drains through a tap into a container under the well. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on height adjustable feet in stainless steel.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Overheat protection thermostat as standard on all units.
- Oil drains through a tap into a drainage container positioned under the well.
- All major compartments located in front of unit for ease of maintenance.
- IPx4 water protection.
- Incoloy armoured heating elements located inside the well can be lifted up for easier cleaning.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.

Construction

- Interior of well with rounded corners for ease of cleaning.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Sustainability

 This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

APPROVAL:



Modular Cooking Range Line EVO700 Two Wells Freestanding **Electric Fryer 14 liter**

Included Accessories

•	2 of Door for open base cupboard	PNC 206342
•	2 of Basket for 14 and 15lt fryers	PNC 921691

2 2 of Basket for 14 and 10th fry 015	1110	021001	
Optional Accessories			
 Junction sealing kit 	PNC	206086	
 4 wheels, 2 swivelling with brake (EV0700/900). It is mandatory to install with base supports for feet/wheels. 	PNC	206135	
 Flanged feet kit 	PNC	206136	
 Frontal kicking strip for concrete installation, 800 mm 		206148	
 Frontal kicking strip for concrete installation, 1000 mm 		206150	
 Frontal kicking strip for concrete installation, 1200 mm 		206151	
 Frontal kicking strip for concrete installation, 1600 mm 		206152	
 Frontal handrail 800 mm 		206167	
Frontal kicking strip, 800 mm		206176	
 Frontal kicking strip, 1000 mm 		206177	
 Frontal kicking strip, 1200 mm 		206178	
 Frontal kicking strip, 1600 mm 		206179	
 Large handrail (portioning shelf) 800 mm 		206186	
 Frontal handrail 1200 mm 		206191	
 Frontal handrail 1600 mm 		206192	
 4 feet for concrete installation (not for 900 line freestanding grill) 	PNC	206210	
 Right and left side handrails 	PNC	206240	
 Pair of side kicking strips 	PNC	206249	
 Pair of side kicking strips (concrete installation) 	PNC	206265	
 Chimney upstand, 800 mm 		206304	
• 2 side covering panels, height 700 mm, depth 700 mm	PNC	206319	
 Door for open base cupboard 	PNC	206342	
 Base support for feet or wheels - 800mm (EV0700/900) 	PNC	206367	
 Base support for feet or wheels - 1200mm (EV0700/EV0900) 	PNC	206368	
 Base support for feet or wheels - 1600mm (EVO700/900) 	PNC	206369	
• Rear paneling - 800mm (EV0700/900)	PNC	206374	
• Rear paneling - 1000mm (EV0700/900)	PNC	206375	
• Rear paneling - 1200mm (EV0700/900)	PNC	206376	
 Chimney grid net, 400mm 	PNC	206400	
 Basket for 14 and 15lt fryers 	PNC	921691	
• 2 half size baskets for 12, 14 and 15lt fryers	PNC	921692	
 Filter for fryer oil collection basin for 7lt, 14lt, 15lt free standing fryers 	PNC	921693	















Modular Cooking Range Line EVO700 Two Wells Freestanding Electric Fryer 14 liter

Front (908 mm EI 2 1/16 ' 2 3/16 27 1/16 " 688 mm 56 mm



EI = Electrical inlet (power) Equipotential screw



Electric

Supply voltage:

372085 (Z7FREH2FF0) 380-400 V/3N ph/50/60 Hz 372144 (Z7FREH2FFN) 230 V/3 ph/50/60 Hz

Total Watts: 17.4 kW

Predisposed for:

380-400V 3N~ 50/60Hz

372085 (Z7FREH2FF0) 15,7-17,4kW

Key Information:

Usable well dimensions (width): 240 mm Usable well dimensions (height): 285 mm Usable well dimensions (depth): 380 mm

Well capacity: 12 It MIN; 14 It MAX **Thermostat Range:** 105 °C MIN; 185 °C MAX

Net weight: 81 ka

Shipping weight:

Side

372085 (Z7FREH2FF0) 83 kg 372144 (Z7FREH2FFN) 101 kg

Shipping height:

372085 (Z7FREH2FF0) 1130 mm 372144 (Z7FREH2FFN) 1140 mm Shipping width: 820 mm Shipping depth: 860 mm Shipping volume: $0.8 \, \text{m}^3$

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Certification group:

EFI7214 372085 (Z7FREH2FF0) 372144 (Z7FREH2FFN) N7FE2









